

海宁市丽彩颜料化工有限公司 Haining Licai Pigment Chemical Co., Ltd.

中国海宁市海昌南路426号 P.C.Code: 314400 426 Haichangnan Road, Haining, China.

Fluorescent Red GK

Color Index: Solvent red 197

Molecular formula: C₂₃H₁₉N₅O

CAS No.: 52372-39-1

Product specification

Appearance Red powder

Tinting Strength 100±3%

Shade Color Similar to the standard, fluorescent red with yellow

shade

Ash ≤ 1.0% Moisture ≤ 1.0% Color Differential Value Δ E ≤ 0.7

Commentary

A fluorescent red with yellow shade, good lightfastness and excellent heat resistance.

Test Items	PS	ABS	SAN	РММА	PC	R-PVC	PA6	PET
Heat resistance temperature, [°] C (0.05% dyes, transparent)	280	280	280	280	280	-	=	-
Heat resistance temperature, $^{\circ}$ C (0.05% dyes + 1.0% Titanium dioxide)	280	260	280	280	280	-	-	ı
Migration resistance	-	-	-	-	-	-	-	-
Light fastness (0.05% dyes, transparent)	7	-	-	-	-	-	-	-
Weather resistance	-	-	-	-	-	-	-	-
Acid resistance (in 5% hydrochloric acid solution)	-	-	-	-	-	-	-	-
Alkali resistance (in 5% caustic soda solution)	-	-	-	-	-	-	-	-

Application Profile

PS	•	HIPS	•	ABS	•
PC	•	PVC-R	•	PMMA	•
SAN	•	AS	•	PA	-
PET	•				

• = recommended \circ = potential use - = not recommended

Disclaimer

All above data are obtained by our best knowledge and regarded as references for you. We strongly recommended a trial test before your mass application.

Technical Data Sheet TDS code: TDS-SR197-1