

海宁市丽彩颜料化工有限公司 Haining Licai Pigment Chemical Co., Ltd.

中国海宁市海昌南路426号 P.C.Code: 314400 426 Haichangnan Road, Haining,China.

Technical data sheet

Product name: Solvent Green 28

Molecular formula: C₃₄H₃₄N₂O₄

CAS No.:

Product specification

Appearance

Tinting Strength 100 2%

Shade Color Similar to the standard

Ash ≤ 0.5% Moisture ≤ 1.0% Insolubles in xylene ≤ 0.5% Color Differential Value Δ E ≤ 0.7

Commentary

A yellow shade green with excellent lightfastness and good heat resistance.

Test Items	PS	ABS	SAN	PMMA	PC	R-PVC	PA6	PET
Heat resistance temperature, $^{\circ}$ C (0.05% dyes, transparent)	300	-	-	300	300	-	=	300
Heat resistance temperature, $^{\circ}$ C (0.05% dyes + 1.0% Titanium dioxide)	300	280	280	280	-	-	-	ı
Migration resistance	-	-	-	-	-	-	-	-
Light fastness (0.05% dyes, transparent)	8	6	-	-	8	-	-	7-8
Weather resistance	-	-	-	-	-	-	-	-
Acid resistance (in 5% hydrochloric acid solution)	-	-	-	-	-	5	=	-
Alkali resistance (in 5% caustic soda solution)	-	-	-	-	-	5	-	-

Application Profile

PS	•	HIPS	•	ABS	•
PC	•	PVC-R	•	PMMA	•
SAN	•	AS	•	PA	-
PET	•				

 \bullet = recommended \circ = potential use - = not recommend

Disclaimer

All above data are obtained by our best knowledge and regarded as references for you. We strongly recommended a trial test before your mass application.

TDS code: TDS-SG28-1